

DECK EQUIPMENT – STARTING PLATFORMS

G. DECK EQUIPMENT

All deck equipment and the Pool Contractor shall furnish related accessories specified herein. Installation shall be by the Pool Contractor unless otherwise dictated by the project drawings. Paddock Pool Equipment Company, Inc., of Rock Hill, South Carolina, shall supply the deck equipment and related accessories. Substitutions may be considered if offered according to the conditions set forth in the appropriate section of these specifications. Products offered by a company not regularly engaged in the manufacture of such equipment shall not be acceptable for this project. The deck equipment shall be guaranteed for a period of one year against defects in workmanship or material.

G. STARTING PLATFORM - DOUBLE COLUMN, PADDOCK MODEL 4909

The Starting Platforms shall be quickly and easily removable without using a wrench or unfastening anchor bolts. The platform frame shall be fabricated from satin finish, 1.9" OD X .120" wall, Type 304 stainless steel tubing. Flush with the front edge of the platform, there shall be a backstroke bar. The backstroke bar shall be fabricated from satin finish, 1.05" OD, Schedule 40, Type 304 stainless steel pipe. A mounting tread shall be positioned off the rear legs. The tread shall have a deeply formed integral, slip resistant surface. The tread shall be firmly attached to the legs by welded stainless steel gussets. At each side of the platform, attached to the legs, shall be a stainless steel plate on which the lane number is displayed with a 4" numeral. The top of the starting platform shall be fabricated of extruded PVC sections and enclosed in a stainless steel frame. The sections shall be white, 1" deep X 5/8" wide with a serrated top surface. The space between sections shall be 1/8".

Two Paddock Catalog No. 4814-SFC anchors, with covers, shall be supplied with each starting platform. The anchor shall be fabricated of stainless steel and the insert cover shall be stainless steel. The anchors shall be provided as a unit on 19" centers, held rigidly together by two #4 rebars.

G. STARTING PLATFORM - TRACK START DOUBLE COLUMN, PADDOCK MODEL 4911

The Starting Platforms shall be quickly and easily removable without using a wrench or unfastening anchor bolts. The platform shall be side mount, 24" wide x 32" long. The frame shall be fabricated from satin finish, 1.9" O.D. x .120" wall, Type 304 stainless steel tubing. Flush with the front edge of the platform, there shall be a backstroke bar. The backstroke bar shall be fabricated from satin finish, 1.05" O.D., Schedule 40, Type 304 stainless steel pipe. A mounting tread shall be positioned off the side of the platform. The tread shall be fabricated from stainless steel, and have a slip resistant surface. At each side of the platform, attached to the legs, shall be a stainless steel plate on which the lane number is displayed with a 4" numeral. Top: The top of the starting platform shall be fabricated of extruded PVC sections and enclosed in a stainless steel frame. The sections shall be white, 1" deep x 5/8" wide with a serrated top surface. The space between sections shall be 1/8".

Anchor: Two Paddock Catalog No. 4814 anchors, with covers shall be supplied. The anchor shall be fabricated of stainless steel and the insert cover shall be stainless steel. The anchors shall be provided as a unit on 19" centers, held rigidly together by two #4 rebars.